# **ONSET**

## **HOBO® MX2201 Data Logger**

### Pendant MX Water Temperature Data Logger

The HOBO MX2201 waterproof temperature logger leverages the power of Bluetooth Low Energy (BLE) to deliver accurate temperature measurements straight to your iOS or Android mobile device. Designed for durability, this compact waterproof logger is ideal for measuring temperature in streams, lakes, oceans, and soil environments. Data collection in the field has never been easier!

#### **Supported Measurements:**

Temperature and Water Temperature



#### **Key Advantages:**

- Convenient wireless setup and download via Bluetooth Low Energy (BLE)
- Large memory stores 96,000 measurements
- Waterproof to 30 meters (100 feet)
- User-replaceable battery
- Mounting tabs for fast, easy deployment
- · LED alarm notifies you when temperature exceeds set threshold
- Works with Onset's free HOBOmobile app
- ±0.5°C (±0.9°F) accuracy

#### **HOBO MX2201 Data Logger Specifications**

Temperature Sensor (MX2201 and MX2202)

Range -20° to 70°C (-4° to 158°F) in air

-20° to 50°C (-4° to 122°F) in water

**Accuracy** ±0.5°C from -20° to 70°C (-4° to 158°F)

**Resolution**  $0.04^{\circ}\text{C} (0.072^{\circ}\text{F})$ **Drift**  $<0.1^{\circ}\text{C} (0.18^{\circ}\text{F}) \text{ per year}$ 

Response Time 17 minutes typical to 90% in air moving 1 m/s, unmounted

7 minutes typical to 90% in stirred water, unmounted

Radio Power 1 mW (0 dBm)

Logger

**Transmission Range** Approximately 30.5 m (100 ft) line-of-sight

Wireless Data Standard Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)

**Logger Operating Range** -20° to 70°C (-4° to 158°F) in air

Logging Rate1 second to 18 hoursBuoyancy (Fresh Water)2g (0.07 oz) positiveWaterproofTo 30.5 m (100 ft)Memory96,000 measurements

Battery CR2032 3V lithium, user replaceable

Battery Life 1 year typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always On in

software.

2 years typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off in

z ycars ty

software.

Faster logging intervals and statistics sampling intervals, burst logging, remaining connected

with the app, excessive downloads, and paging may impact battery life.

To ensure proper battery installation, see Battery Information for detailed instructions on

replacing the battery.

**Time Accuracy** ± 1 minute per month at 25°C (77°F)

Full Memory Download Approximately 45 seconds; may take longer the farther the device is from the logger

Wetted Materials Polypropylene case, EPDM O-ring

**Dimensions** 3.35 x 5.64 x 1.8 cm (1.32 x 2.22 x 0.69 inches)

**Weight** 12.75 g (.45 oz)

The CE Marking identifies this product as complying with all relevant directives in the European Union (EU). This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.

#### **Contact Us**

Sales (8am to 5pm ET, Monday through Friday)

- ► Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ► Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation 470 MacArthur Boulevard Bourne, MA 02532