



HOBO[®] H21-USB Data Logger

USB Micro Station Data Logger

Rugged and compact, the redesigned HOBO USB Micro Station is a weatherproof data logger for multi-channel monitoring of microclimates. Starting at just \$220, this battery-powered station accepts up to five plug-and-play Smart Sensors and has a hinged door to make sensor installation simple and quick. The Micro Station is equipped with a built-in USB port for fast, efficient data readout to a computer, and an integrated mounting tabs for easy installation.

Looking for a cellular option? The MicroRX Station offers integrated solar panel or battery-power for affordable remote data offload via 4G cellular.

Interested in water level and flow monitoring? The MicroRX Water Level Station combines the MicroRX Station with Onset's own water level sensor and pre-programmed water flow formulas.

Supported Measurements:

4-20mA, Amp Hour (Ah), Barometric Pressure, DC Voltage, Kilowatt Hours (kWh), Leaf Wetness, Light Intensity, Power Factor (PF), Pulse Input, Rainfall, Relative Humidity, Soil Moisture, Temperature, Volt-Amp Reactive, Volt-Amp Reactive hour, Volt-Amps (VA), Water Flow, Watt Hours (Wh), Watts (W) and Wind

Key Advantages:

- Compact size for easy deployment
- Weatherproof IP66 enclosure for harsh environments
- Direct USB offload--no need for an adapter cable
- Includes five smart sensor inputs
- Hinged door and integrated mounting tabs
- Runs for up to a year on four standard AA batteries
- Compatible with HOBOWare and HOBOWare Pro software for logger setup, graphing and analysis



HOBO H21-USB Data Logger Specifications

Logger	
Operating Range	-20° to 50°C (-4° to 122°F) with alkaline batteries -40 to 70°C (-40 to 158°F) with lithium batteries
Smart Sensor Connectors	5
Smart Sensor Data Channels	Maximum of 15 (some smart sensors use more than one data channel; see sensor manual for details)
Smart Sensor Network Cable Length	100 m (328 ft) maximum
Logging Interval	1 second to 18 hours
Start Modes	Immediate, at interval, push button, or delayed start
Memory Modes	Stop when full or wrap when full
Memory	512 KB nonvolatile flash data storage
Time Accuracy	0 to 2 seconds for the first data point and ±5 seconds per week at 25°C (77°F)
Battery Type	Four AA 1.5 V alkaline batteries for operating conditions of -20° to 50°C (-4° to 122°F); four AA 1.5 V lithium batteries for operating conditions of -40 to 70°C (-40 to 158°F)
Battery Life	1 year, typical use (up to five sensors with 1 minute or greater logging interval)
Communication Type	USB 2.0 interface
Full Memory Download Time	4 minutes
Enclosure Access	Hinged door secured by one latch with eyelet for use with user-supplied padlock
Materials	Outer enclosure: Polycarbonate/PBT blend with stainless steel hinge pins; Gaskets: Silicone rubber; Cable channel: EPDM rubber
Dimensions	17.04 x 11.94 x 4.47 cm (6.71 x 4.70 x 1.76 in.) see diagrams in manual Padlock hole diameter: 0.58 cm (0.23 in.)
Weight	414g (14.6 oz.)
Environmental Rating	Weatherproof enclosure, NEMA 4X and IP66
CE	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532