



## T-VER-971BP-200 Sensor

### Split-Core Bi-Polar DC Transducer Sensor

Split-Core Bi-Polar DC Transducer sensor that measures up to 200 Amps of DC current in both flow directions.

Requires analog port selection during U30 system configuration and use of a S-FS-CVIA when using the H22-001 data logger. When using a U12 data logger, this sensor requires a 4-20mA input cable (CABLE-4-20mA) and external power provided by an AC adapter (AC-SENS-1). When configuring this with an RX3000 system, it requires a analog module (RXMOD-A1).

Note: For measurements larger than 120A the device must be powered by a minimum of 15V to maintain expected accuracy.

[View Veris manual for T-VER-971BP-200](#)

#### Supported Measurements:

DC Current

#### Key Advantages:

- Measures current flow in both directions which is especially beneficial for Solar PV applications.
- Adjustable span range
- Small size, split-core for ease of installation



## T-VER-971BP-200 Sensor Specifications

### DC Amperage (bi-polar)

**Measurement range:** +/- 2 to +/- 200 (via span adjust)

**Accuracy (below 100A span):** +/- .5 A

**Accuracy (above 100A span):** +/- .5% full scale

**Sensor supply:** 12 - 24 DC (15 VDC min. for currents > 120 A), 35 mA no-load to 110 mA at 200 A current

**Isolation:** 600 VAC rms

**Operating temperature range:** -30 to 60C (-22 to 140F)

**Humidity range:** 10 - 90% non-condensing

**Response time:** 2 sec.

**Output:** (bi-polar) 4 - 20mA

**Dimensions:** 3.1x2.8x1.4 in. (79x70x36 mm)

**Weight:** 5.25 oz.

**Sensor opening:** 1.1x.9 in. (28x23 mm)

**LED indications:** single green blink=Norm, double green=Over Span, red+green=Over Limit, solid red=overload

**CE, UL**

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
470 MacArthur Boulevard  
Bourne, MA 02532