

T-MAG-SPT-150 Sensor Specifications

Measurement range: 150, 300, 600 Volts AC

Accuracy: $\pm 1\%$ (from 10% to 130% of rated voltage)

Phase angle: < 1 degree

Output signal to FlexSmart Module: 0.333 Volt at rated input voltage

Connections: 8-ft PVC insulated wire, UL1015

High voltage input: #14 AWG, blue/brown

Low voltage output: #22 AWG twisted pair, black/white

Construction: Epoxy filled ABS plastic

Dimensions: 5.5 cm x 3.9 cm x 3.1 cm (2.2" x 1.6" x 1.2")

Weight: 491.2g (17.33oz)

Number of data channels: 1

To download the manual from Magnelab click [here](#).

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532